

## CE TYPE APPROVAL CERTIFICATE

n. **001164303/OE**

2016/10/24

This CE-Certificate CANCELS & REPLACES the previous one nr. 001142405/OE dated 2014/06/12.

This is to certify, that the hereunder described items of Personal Protective Equipment have overcome positively the "CE type examination", proving their conformity to the safety and health requirements of the Directive 89/686/EEC.

|   |   |   |
|---|---|---|
| Manufacturer:<br>(Responsible of the PPE) | <b>GIASCO s.r.l.</b><br>via Zaupa, 50 36072 CHIAMPO (VI) - ITALIA   |   |
| Type of PPE:                              | <b>Safety footwear</b> in conformity with <b>EN ISO 20345:2011 class I</b><br>(= footwear in leather and other materials, excluding all-rubber or all-polymeric footwear).  |   |
| Category of PPE:                          | <b>II:</b> Personal Protective Equipment against "medium" risks.<br>This certificate is based on the reference standards listed below: its validity is no longer ensured should new version of the standards come into force.   |   |
| Model                                     | <b>"AC003D"</b><br>product line: ACTION   |   |
| Description:                              |  <p><u>model:</u> A (low shoe);<br/><u>fastening system:</u> by means of laces;<br/><u>processing:</u> direct injection;<br/><u>sole:</u> black compact PU marked ACTION ANTISHOCK ANTISLIPPING ANTISTATIC OIL RESISTANT MADE IN ITALY;<br/><u>midsole:</u> dark grey PU foam;<br/><u>upper:</u> black split leather print nappetta declared thickness 1,8/2,0 mm (MP 10011D) with a lateral insert made of dark grey suede split leather 1780 declared thickness 1,8/2,0 mm (MP 20100T) and an orange insert made of suede split leather 17623 (MP 20100AR);<br/><u>collar:</u> black fabric coated in PU REIKI declared thickness 0,8 mm (AC 20805 B);<br/><u>tongue/bellows:</u> made of the same fabric of the collar, centrally lined and padded, with a reinforcement made of the same leather of the upper (MP 20100T);<br/><u>vamp lining:</u> grey felt IBILINE 7121 91S (AC 20890 Q1);<br/><u>rear lining:</u> black Thorelle fabric matched with MTP 3,0 mm (AC 20876 B);<br/><u>lining of both collar and upper tongue:</u> light grey SURF fabric (AC 20826Q1); same fabric in orange colour 487 in the seat region (AC 20826AR);<br/><u>insole:</u> white multi-layered fabric marked "ZERO PERFORATION SLIM K18.0/3 SLIM" (cod. AC20740), which also serves as penetration resistant insert;<br/><u>heel seat lining:</u> black faux non woven fabric cambrelle 4000 matched with dark grey PE foam (AC 20405);<br/><u>toecap:</u> polymeric material art. PS 101(AC 10781).</p> |   |
| Technical Standard:                       | <p><b>EN ISO 20344:2011</b><br/>(UNI EN ISO 20344:2012)</p> <p><b>EN ISO 20345:2011</b><br/>(UNI EN ISO 20345:2012)</p>   | <p>Personal protective equipment – Test methods for footwear</p> <p>Personal protective equipment – Safety footwear</p> |
| Intended use:                             | general industry, engineering industry, agriculture, warehouses, works on trucks, cranes.   |   |
| Size range:                               | from 39 to 47.  |   |
| Technical File:                           | <b>DC-8101/E</b> (including Application to <b>RCT</b> and Technical Documents).   |   |
| Test report:                              | <b>RCT n°354229/E.</b>  |   |
| Basis of evaluation:                      | applicable requirements of European Directive 89/686/EEC and reference Standards.   |   |

## CE TYPE APPROVAL CERTIFICATE

n. **001164303/OE**

2016/10/24

This CE-Certificate CANCELS & REPLACES the previous one nr. 001142405/OE dated 2014/06/12.

Functions and performance levels:

**basic requirements for safety footwear (SB)** (see Table 2 and 3 of EN ISO 20345:2011): all mandatory ones, among which:

**SRC = Slip resistance** - meets the following requirement:

- surface: ceramic / lubricant: detergent solution;
- surface: steel / lubricant: glycerol.

**Additional requirements** (Tab.18 and 20 of EN ISO 20345:2011):

**S3** = closed seat region, antistatic properties, energy absorption of seat region, resistance to fuel oil, water penetration resistance and absorption (water-repellent upper), penetration resistance, cleated outsole.

**Note: [1]** the penetration resistance of the synthetic stitch proof insole tends to decrease with the diameter of the perforating object; in return the synthetic insole offers more protective surface and ergonomics advantages (flexibility, insulation, humidity and impact absorption).

**[2]** the footwear also meets the requirement in accordance with IEC 61340-4-3:2001 for the electrical resistance **ESD class 3** (electric dissipative footwear).

Marking:

on a stitched label and displaying the following information:

(see example below)

- **CE Marking** attesting PPE conformity to all the provisions of the Directive 89/686/EEC (and any subsequent amendments);
- Name of the Manufacturer (on the tongue);
- designation of the footwear (alphanumeric code: unique/unambiguous);
- Technical Harmonized Standard of reference;
- safety symbols;
- size of the footwear (printed on the outsole);
- date of production (printed on the outsole with clock indicator).

**CE UNI EN ISO 20345: 2012**  
**S3 SRC AC003D**  
**ESD class 3**



Note: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements. The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).