



LUTON 03 FO

C70680C

CE UNI EN ISO 20347:2012 O3 FO SRC ESD

High occupational shoe, MICROWASH thickness 1,8-2,0 mm. Perspiring and abrasion resistant fabric lining. Shoe with refracting fabric insert.

Soft, lined and padded tongue.

MIDSOLE flexible antiperforation composite fabric according to FN 12568

SOLE CITY bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, antishock and anti-slipping **SRC**

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial **FO** sole resistance to hydrocarbons

The shoe satisfies the requirement according to the norm IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for the electrical resistance $\pmb{\mathsf{ESD}}$

Size 36-47 Shoe weight Sz 42 gr. 540



CERTIFICATIONS











TECHNOLOGIES AND MATERIALS













SECTORS

LOGISTICS AND LIGHT INDUSTRY & ESD AREAS TOOD, HOSPITAL AND HYGIENE HOTELS, RESTAURANTS & CATERING

SOLE



City is a **unique styled** shoe, perfect for people who look for a safety shoe to use in a lot of different situations, **free time** included.

TEST RESULTS	request	results
SRA	11551 > 0.00	2.44
ceramic +	HEEL $\geq = 0.28$	0,41
NaLS	FLAT $\geq = 0.32$	0,44
SRB		
steel +	HEEL \geq = 0,13	0,20
glycerol	FLAT ≥ = 0,18	0,23

PLUS



MICROWASH
MICRO WASH is a Chrome free material finished with perspiring polyurethanes. Very light and perspiring, it is suitable for alimentary et hospital sectors. It is also studied for people wearing the shoes for a lot of hours on wet surfaces. Il resists to acids, mostly oleic acid. It is washable with water and neutral soap at 40°.