



UNIVERSE

S3L FO SC SR

3L135SA

EN ISO 20345:2022+A1:2024 S3L FO SC SR ESD

LOW SAFETY SHOE

36-47

3CLOUD Elasticity

Low safety shoe, made of high tenacity fiber, breathable and abrasion resistant WPA

Cover tip in TPU ideal to counteract abrasions.

Heel GIASCO 3PU PATENT offers stability, comfort and lightness to the shoe.

Soft, lined and padded tongue.

Equipped with adjustable elastic and self-locking, quick opening.

"The shoe is also provided with the classic lace."

COMPLETELY METAL FREE SHOETOECAP

200J polymeric composite non-thermic according to EN 22568

PL MIDSOLE flexible antiperforation composite fabric according to EN 22568

3CLOUD sole polyurethane three density anti-static, hydrolysis resistant ISO 5423:92,

to hydrocarbons and abrasion, shock-resistant and slip-resistant

INSOLE YEAH, extra comfort in closed-cell polyurethane compound patented DryGo! ®

DryGo! ® polyurethane absorbs moisture from the foot and vaporizes it quickly.

Also thanks to the high anatomical, self-molding and resilience properties of polyurethane, this insole gives a prolonged well-being. Breathable, removable, anatomical, absorbent, antibacterial and ESD.

Footwear meets the requirement in accordance with IEC 61340-4-3:2017 (IEC 61340-5-1:2024) for electrical resistance ESD

FO sole resistance to hydrocarbons




SR sole resistance against slipping




Size 36-47 Shoe weight Tg 42 gr.500



AREAS OF APPLICATION

-  Construction and Building Sites
-  Logistics and Light Industry
-  Automotive Components
-  Metal and Wood Carpentry
-  ESD Area








CERTIFICATIONS APPLIED

-  Water Penetration and Absorption (WPA)
-  Slip Resistance (mandatory ceramic-Nals test)
-  Hydrocarbon Resistance

-  PL Puncture Resistance with Non-Metallic Insert (nail Ø 4.5mm)
-  Antistatic Footwear
-  DGUV 112-191

-  Toe Cap Abrasion Resistance
-  Heel Energy Absorption

TECHNOLOGIES AND MATERIALS

-  No metal
-  Quick Release
-  Three to be™ - Triple Density Injection
-  ESD - Electrostatic Discharge
-  Slip Resistance (optional glycerin test)
-  Mondo Point 11
-  Technical Fabric

ANTI-SLIP RESULTS

\*after simulation of walking by slight abrasion

Ceramic tile floor with NaLS	<div>Forward Heel (heel slip 7°)</div> <div>≥ 0.31 ≥ 0.48</div>	<div>Backward heel (heel slip 7°)</div> <div>≥ 0.36 ≥ 0.50</div>	Ceramic tile floor with glycerin	<div>Forward Heel (heel slip 7°)</div> <div>≥ 0.19 ≥ 0.32</div>	<div>Backward heel (heel slip 7°)</div> <div>≥ 0.22 ≥ 0.37</div>
------------------------------	---	--	----------------------------------	---	--



**Three to be™ - Triple Density Injection**

Three to Be® - Tripla Densità Iniettata technology represents one of the most advanced results of our R&D efforts. Patented by Giasco, it integrates three entirely polyurethane-injected sole layers to optimize safety shoe performance in terms of comfort, stability, and slip resistance.

**3CLOUD Elasticity**

3Cloud and its distinctive through-holes in the sole have been meticulously designed to provide unique comfort for safety footwear in indoor environments. Specifically, the tunnels running perpendicularly through the midsole offer both a pleasant cushioning effect and high rebound. These features are maintained throughout the entire life of the safety shoe thanks to the polyurethane's strong "memory" property and especially the trapezoidal geometry of the holes. Together, these aspects minimize sole deformation over time. Finally, the outsole of this safety shoe features a dual tread pattern: one inspired by racing tire technology, and the other hexagonal with a "suction cup" effect. Both systems work together to ensure maximum grip on smooth and regular surfaces.

