



Chemical protection

ULTRANE0 382

Frequent contact | ultra-comfort wear

Maximum comfort and chemical protection



CHEMICAL PROTECTION
TYPE A

SPECIFIC ADVANTAGES

Thermal protection

- Added comfort and thermal insulation, due to the cotton-knit lining



Comfort

- Extremely supple, due to the unique Mapa multi-layer process



Productivity

- Embossed texture for better grip on wet objects



Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting



Additional benefits

- Available in vending machine packaging

INDUSTRIES

- Automotive/mechanical industry
- Chemical industry
- Other industries

APPLICATIONS

- Engine part assembly
- Surface treatment
- Chemical product blending
- Handling drums of chemical products
- Manipulating valves
- Laboratory tests
- Machine maintenance



EN388
2121X

EN ISO 374-1
TYPE A



ALMNST



EN ISO 374-5

DEXTERITY
EN 420:

5/5



EN407
X1XXXX



CAT.3

0334



Chemical protection

ULTRANE0 382

Frequent contact | ultra-comfort wear

LEGENDS

EN388		MECHANICAL HAZARDS	
PERFORMANCE LEVELS (X = NOT TESTED)			
2	1	2	1 X
0-4	0-5	0-4	0-4 A-F P
Abrasion resistance			
Blade cut resistance			
Tear resistance			
Puncture resistance			
Cut resistance according to ISO 13997			
Impact protection (optional)			

EN407		THERMAL RISKS (HEAT AND FIRE)	
PERFORMANCE LEVELS (X = NOT TESTED)			
X	1	X	X X X
0-4	0-4	0-4	0-4 0-4 0-4
Burning behaviour			
Contact heat resistance			
Convective heat resistance			
Radiant heat resistant			
Resistance to small drops of molten metal			
Resistance to large quantities of molten metal			

EN ISO 374-1		CHEMICAL RISKS	
TYPE A			
A: Methanol			
L: Sulphuric acid 96%			
M: Nitric acid 65%			
N: Acetic acid 99%			
S: Hydrofluoric acid 40%			
T: Formaldehyde 37%			

EN ISO 374-5		MICRO-ORGANISMS	
Protection against bacteria and fungi			

PRODUCT DETAILS

Interior finish	Textile support Mapa Technology
Exterior finish	Embossed texture
Material	Polychloroprene
Cuff characteristic	Feston Cuff
Colour.s	Blue
Length (cm)	36
Thickness (mm)	0.90
Size	6 7 8 9 10
Surface resistance according to EN1149-1 (Value in palm area at 25% HR)	1.5E+11 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% HR)	5.2E+10 Ω

LOGISTIC DETAILS

Packaging	12 pairs/bag 72 pairs/carton
-----------	---------------------------------

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1646 updated 01-20/11/2019
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France